

Pos. Tag - ID	Description	Quantity	Unit	Price (EUR) Total
0	<p>7ML7580-0PC10-4BK0-Z E47</p> <p>SITRANS LR580 Flanged lens antenna: Continuous, non-contact, 120 m (394 ft) range, for solids or liquids.</p> <p>0 Communications: 4 ... 20 mA, HART</p> <p>0 Sealing material of the antenna/process connection: PEEK / FKM / #40...+150 °C (-40...+302 °F)</p> <p>PC Process connection type and material: Flange: DN80 PN16, flat face, 316/316L</p> <p>1 Second line of defence (SLOD) gas-tight seal: SLOD included</p> <p>0 .</p> <p>4 Enclosure: Single compartment enclosure</p> <p>B Type of protection: Intrinsically safe Ex ia / IS (Class I, II, III, Division 1)</p> <p>K Electrical connection: 1/2" NPT</p> <p>0 Local HMI: None, with blind lid</p> <p>E47 Regional Ex Approval: ATEX (Europe), IECEX (Wordwide)</p> <p>Netweight: 7.000 KG Delivery time (working days): 30 plus transportation time Price group: 8L2 Fab Group: 4716 LKZ: CA AL: N ECCN: 5A991X Commodity code: 9031800090</p>	1	PC	on demand

Total Price **on demand**
