

Pos. Tag - ID	Description	Quantity	Unit	Price (EUR)
				Total
0	<p>7ME4464-3FJ11-2CB3-Z A11+B01+E06+F11+L60</p> <p>The Coriolis flowmeter with superior performance under demanding conditions. This meter delivers unsurpassed performance for demanding and critical applications with superior aeration handling and advanced diagnostic functionality. The Coriolis meter with the most robust and durable design for precise measurement in high pressure applications.</p> <p>4 Coriolis sensor FCS600 with transmitter FCT040</p> <p>3F Sensor size 1" DN25, tube material 316L, Process connection 316L, connection size 1 1/2" DN40</p> <p>J1 JIS G3447 / ISO2852 Clamp</p> <p>1 Media temperature Compact -50 # 150 °C (-58 # 302 °F), Remote -70 # 150 °C (-94 # 302 °F)</p> <p>2 Massflow: 0.1%, Density: 1 g/l</p> <p>C Remote type with "urethane-cured polyester powder coating" coated aluminum transmitter housing and standard neck sensor</p> <p>B ATEX, explosion group IIC and IIIC II 2D Ex ib IIIC T150 °C Db (Sensor)</p> <p>3 With Display</p> <p>A11 NPT, No glands (1/2")</p> <p>B01 Stainless steel 1.4301/304, 1.4404/316L</p> <p>E06 4-20 mA HART active</p> <p>F11 1 passive pulse or status output</p> <p>L60 20meter (65.6ft) remote connecting cable terminated standard gray / Ex blue</p> <p>Netweight: 1.000 KG            Delivery time (working days): 24 plus transportation time            Price group: 8F5            Fab Group: 4833            LKZ: DE            AL: N            ECCN: N            Commodity code: 90261021</p>	1 PC		on demand
<b>Total Price</b>				<b>on demand</b>

